

Carpet boom

30 TTD

type	diameter mm	length mm	capacity ... kg/mm LSP (LC)								B m	V LLC mm	ESP COG mm	weight kg	ISO
			500 mm	1000 mm	1250 mm	1500 mm	1750 mm	2000 mm	2250 mm	2500 mm					
30 TTD	60	2000	1285	640	515	430	370	320	285	260	400	100	360	130	II
30 TTD	60	3000	1285	640	515	430	370	320	285	260	400	100	675	152	II
30 TTD	60	4000	1285	640	515	430	370	320	285	260	400	100	1035	174	II
30 TTD	70	2000	2040	1020	815	680	580	510	455	410	400	100	430	145	II
30 TTD	70	3000	2040	1020	815	680	580	510	455	410	400	100	785	175	II
30 TTD	70	4000	2040	1020	815	680	580	510	455	410	400	100	1180	205	II
30 TTD	75	2000	2510	1255	1005	835	720	630	560	500	400	100	465	155	II
30 TTD	75	3000	2510	1255	1005	835	720	630	560	500	400	100	840	190	II
30 TTD	75	4000	2510	1255	1005	835	720	630	560	500	400	100	1250	225	II
30 TTD	80	2000	3040	1520	1220	1015	870	760	680	610	400	100	405	205	III
30 TTD	80	3000	3040	1520	1220	1015	870	760	680	610	400	100	750	245	III
30 TTD	80	4000	3040	1520	1220	1015	870	760	680	610	400	100	1135	285	III
30 TTD	90	2000	4100	2005	1605	1340	1145	1000	890	800	400	100	460	225	III
30 TTD	90	3000	4100	2005	1605	1340	1145	1000	890	800	400	100	830	275	III
30 TTD	90	4000	4100	2005	1605	1340	1145	1000	890	800	400	100	1240	325	III
30 TTD	100	2000	5500	2750	2200	1830	1570	1375	1220	1100	600	120	400	324	IV
30 TTD	100	3000	5500	2750	2200	1830	1570	1375	1220	1100	600	120	735	386	IV
30 TTD	100	4000	5500	2750	2200	1830	1570	1375	1220	1100	600	120	1120	448	IV
30 TTD	120	2000	7800	3900	3120	2600	2230	1950	1735	1560	600	120	485	378	IV
30 TTD	120	3000	7800	3900	3120	2600	2230	1950	1735	1560	600	120	870	467	IV
30 TTD	120	4000	7800	3900	3120	2600	2230	1950	1735	1560	600	120	1290	556	IV

- length of the boom should be 70% of the length of the roll
- lengths of more than 4000 mm upon request
- quick release hooks see accessories
- quick release hooks: class 2, class 3, class 4 upon request



DURWEN 
Forklift Attachments

More than 60 years experience